

FE1010-4P2E

4FE PoE + 2FE Uplink Long Range PoE Switch

Highlights

- 4FE PoE + 2FE Uplink PoE Switch
- 1-4 10/100Mbps RJ45 support the 802.3af/at (PoE+)
- Support IEEE 802.3i, 802.3u, 802.3x, 802.3at, 802.3af, 802.3z
- Up to 30W PoE power for each port
- Support 2K MAC address
- Plug-and-play, no management required



Specifications

Model	FE1010-4P2E
Hardware Specifications	
Ports	6x 10/100M RJ45 ports
Power Supply	AC 100-240V 50/60Hz
Protocol Standards	IEEE 802.3i, 802.3u, 802.3x, 802.3at, 802.3af
Indicator Light	PoE indicators, Link/act indicators, Power
Network Medium	10Base-T: UTP category 3, 4, 5 cable (max. 100m) 100Base-Tx: UTP category 5, 5e cable (max. 100m)
Dimensions	200mm x 119mm x 44.5mm
Lightning Protection Level	6kv
PoE Port	4x 802.3at/af standard PoE ports
PoE Pin Definitions	1/2(+), 3/6(-)
PoE Power	60W
Total power	65W
Forwarding Mechanism	Store-and-Forward
Switching Capacity	1.2Gbps
Forwarding Rate	0.8928Mpps
MAC Address Table	4K
Environment	Operating Temperature: 0°C ~45°C Storage Temperature: -40°C ~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing