

GE1210-24P4C4S

24-port GE + 4-port Combo + 4-port 1G SFP Unmanaged PoE Switch

Highlights

- 24x GE 802.3af/at PoE(PoE+) + 4x Combo + 4x 1G SFP fiber interfaces
- IEEE 802.3x Full-duplex and Back-pressure half-duplex
- All RJ45 ports support IEEE 802.3af/at **PoE(30W/400W)**
- **56Gbps** Switching Capacity
- Support **8K** MAC address



Specifications

Model	GE1210-24P4C4S
Hardware Specifications	
Power Supply	AC 100~240V 50/60Hz
LED Indicators	Link-Act / Speed / Power
Dimensions	440mm x 290mm x 45mm
Ethernet Interface	24x 10/100/1000Mbps RJ45, 4x Combo ports
PoE port	24x IEEE 802.3at/af Power over Ethernet(Up to 30W)
Total PoE Power Budget	400W
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3x, IEEE 802.3cb, IEEE 802.3z, IEEE 802.3at, IEEE 802.3af
Fiber Interface	4x 1000Mbps SFP slots
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100m) 100BASE-TX: Cat5,5e UTP(≤100m) 1000BASE-T: Cat5e,6 UTP(≤100m) 1000BASE-SX: 62.5um MMF(≤275m) or 50um MMF(≤550m)
Switching Specifications	
Transmission Method	Store-and-Forward
Switching Capacity	56Gbps
Packet Forwarding Rate	41.664Mpps
Packet Buffer	4.1Mbit
Jumbo Frame	10K bytes
MAC Address Table	8K
Environment Specifications	
Operating Temperature	0°C ~ 45°C
Operating Humidity	10% ~ 90%(non-condensing)
Storage Temperature	-40°C ~ 70°C
Storage Humidity	5% ~ 95%(non-condensing)