

GE2511-4P1S

5x 2.5GE and 1x 10G SFP+ Unmanaged PoE Switch

Highlights

- 5x 10/100/1000/2500BASE-TX RJ45, 1x 10Gbps SFP+ interfaces
- Port 1-4 Support 802.3af/at 30W PoE
- 5x Auto-Negotiation, Auto-MDI/MDIX Ethernet ports
- Fanless design ensures quiet operation



Specifications

Model	GE2511-4P1S
Hardware Specifications	
Power Supply	DC 54V/1.2A
Protocol Standards	IEEE 802.3, 802.3u, 802.3ab, 802.3bz, 802.3x, 802.3cb, 802.3af, 802.3at
Ports	5x 10/100/1000/2500Mbps RJ45 ports, 1x 10G SFP+ slots
Indicator Light	5x 10/100/1000M/2.5G Link/act, 5x 2.5G Port speed, Power, SFP ports Link/act
Network Medium	10Base-T: UTP category 3, 4, 5 cable (max. 100m) 100Base-Tx: UTP category 5, 5e cable (max. 100m) 1000Base-T: UTP category 5e, 6 cable (max. 100m) 2.5GBase-T: UTP category 5e, 6 cable (max. 100m) 1000BASE-SX: 62.5um MMF (2m~275m) or 50um MMF (2m~550m) 1000BASE-LX: 62.5um/50um MMF (2m~550m) or 9um SMF (2m~5000m) 10GBASE-SR: OM1/OM2/OM3 or above MMF (2m~300m) 10GBASE-LR: IEC's B1.1 and B1.3 SMF (2m~10000m)
Dimensions	160mm x 95mm x 30mm
PoE Port	4x IEEE 802.3at/af standard PoE ports
PoE Pin Definitions	1/2(+), 3/6(-)
PoE Power	60W
Forwarding Mechanism	Store-and-Forward
Switching Capacity	45Gbps
Packet Forwarding Rate	33.48Mpps
Jumbo Frame	10KBytes
MAC Address Table	4K
Environment	Operating Temperature: 0°C ~45°C Storage Temperature: -40°C ~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing