

GET100-4P1G

5x 10G RJ45 Ports Unmanaged PoE Switch

Highlights

- 5x 100M/1000M/2.5G/5G/10G auto-sensing RJ45 ports
- Port 1-4 Support 802.3af/at 30W PoE
- Plug and play
- All ports have wire-speed forwarding capability



Specifications

Model	GET100-4P1G
Hardware Specifications	
Power Supply	AC 100-240V 50/60Hz
Protocol Standards	IEEE 802.3, 802.3u, 802.3ab, 802.3bz, 802.3x, 802.3cb, 802.3af, 802.3at
Ports	5x 100M/1000M/2.5G/5G/10G RJ45 ports
Indicator Light	5x Link/act indicators, 5x 10G speed indicators, Power
Network Medium	100Base-Tx: UTP/STP category 5, 5e cable (max. 100m) 1000Base-T: UTP/STP category 5e, 6 cable (max. 100m) 2.5GBase-T: UTP/STP category 5e, 6 cable (max. 100m) 5GBase-T: UTP/STP category 5e, 6 cable (max. 100m) 10GBase-T: UTP category 6cable (max. 55m), 7 cable (max. 100m)
Dimensions	271mm x 182mm x 45mm
PoE Port	4x IEEE 802.3at/af standard PoE ports
PoE Pin Definitions	1/2(+), 3/6(-)
PoE Power	65W
Total Power	96W
Forwarding Mechanism	Store-and-Forward
Switching Capacity	100Gbps
Packet Forwarding Rate	74.4Mpps
Jumbo Frame	12KBytes
MAC Address Table	16K
Environment	Operating Temperature: 0°C ~45°C Storage Temperature: -40°C ~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing