

## NG-GE62S1000

8-port large sized MQTT based enterprise gateway

### Highlights

- 5-port 10/100/1000/2500Mbps RJ45 interfaces
- Large sized enterprise gateway based on MQTT protocol
- Support PPPoE/DHCP/Static IP access
- Work with different ISP Ethernet access



### Specifications

<b>Model</b>	NG-GE62S1000
<b>Hardware Specifications</b>	
<b>CPU</b>	Intel J6413 4 Core, 10nm, 1.8GHz, 1.5M Cache
<b>Memory</b>	3200MHz DDR4 SO-DIMM
<b>Size</b>	8GB
<b>Storage Type</b>	General SATA, HDD, CF
<b>Interface</b>	1x 6Gb/s SATA
<b>CF</b>	1x CF TypeII slot, default 1G SLC CF card
<b>HDD</b>	Support 1x 2.5" Hard drive bracket with hard drive shockproof function
<b>mSATA</b>	1x mSATA SSD slot (or CF alternative)
<b>Network Specifications</b>	
<b>Heat Dissipate</b>	Super silent ball fan
<b>Ports</b>	5x 10/100/1000/2500Mbps WAN ports (can set to LAN port) 1x 10/100/1000Mbps LAN port 2x USB3.0 Ports 2x 1G SFP ports 1x Console Port
<b>Display port</b>	1x DB-15 VGA, support hot plug
<b>LED Indicator</b>	Layer 1: Hard disk indicator light: Yellow light, flashing when data is read or written Layer 2: Power indicator light: green, power on LED is on Layer 3: green, SFP1 first optical port indicator light Layer 4: green, SFP2 second optical port indicator light
<b>Power</b>	AC 100V-264V
<b>Watchdog</b>	Supports 1-255 second programmable software watchdog and system reset
<b>Power Consumption</b>	65W
<b>Dimension</b>	294mm x 430mm x 44.5mm
<b>Working Temperature</b>	-0°C ~ 50°C
<b>Storage Temperature</b>	-40°C ~ 70°C
<b>Working Humidity</b>	5% ~ 97%RH (No condensation)
<b>Firmware Specifications</b>	
<b>Gateway</b>	Multiple WAN allow multiple ISP network access, Ethernet backup and Network overlay, line detection Support DHCP, DHCPv6, static and PPPoE operation mode Support IPv4 and IPv6 Support DNS, DHCP server, Static routing, ARP binding, Static DHCP
<b>AP Management</b>	Max to access and manage 1024 users Max to manage 1000PCS wireless AP in centrally and remotely, or in AP group Configure wireless AP SSID, password, security, bandwidth, RF power, time, reboot, reset, firmware upgrade, kvr seamless roaming, 5G prior, network topology User's status checking

# NG-GE62S1000

8-port large sized MQTT based enterprise gateway

## Specifications

Firmware Specifications	
<b>Smart Flow Control</b>	No-configuration intelligent flow control, P2P blocking Powerful port routing, domain routing based on TCP, UDP, ICMP and IPMPv6 Support load balance and ISP flow control
<b>VPN</b>	Support VPN client and VPN server Support PPTP, L2TP, IPsec and OpenVPN
<b>Defense Center</b>	Monitoring the device working status from DHCP server, PPPoE server, IP and Loop status Examine the working status from checking status of hard disk, memory, WAN, DHCP server, PPPoE server and IP confliction. Send the working alert by email
<b>Firewall</b>	TCP/UDP/ICMP flood defense Port and host mapping, deny/accept network access based on IP address and MAC address Support DMZ, LAN forward and Share-Net block
<b>Authentication</b>	Portal auth; 3rd Radius billing auth; Account auth, SMS auth; WiFidog Auth, Local Auth and PPPoE server Auth
<b>Management</b>	Web/HTTPS/Telnet management Reboot/Reset/backup/firmware upgrade Remote management by cloud
<b>Others</b>	Network topology auto generation, CA Configuration, build in NTP server