

NHC-24128K

128-ch Full Real Time 4U 24HDDs Smart NVR

Highlights

- **128**-ch IP video input
- **640M** Incoming bandwidth
- 1x **HDMI** output, 1x VGA output
- H.264/H.265/**H.265+**
- 24x SATA interfaces(up to **8TB**)



Specifications

128CH

H.265+

192TB

Model	NHC-24128K
Video and Audio	
Video Input	128-ch 4K/5MP/3MP/2MP/960P
Incoming Bandwidth	640M
Video Output	1-ch HDMI(4KP@30Hz), 1-ch VGA(1080P@60Hz)
Audio Input and Output	IPC Complex audio input, 1-ch RCA Audio Input / HDMI audio output, 1-ch RCA Audio Output
Decoding	
Video Compression	H.264/H.265/H.265+
Synchronous Playback	4-ch 8MP / 9-ch 3MP / Max 16-ch 2MP
Alarm Management	
Alarm Port	RS485(4 in 4 out)
Schedule Type	Continuous, Schedule, Manual
Event	Motion Detection Alarm, Video Loss Alarm, Video Tampering Alarm (e-fence detection, human detection, line crossing, absent alarm, e-bike detection)
Action	Record, Email, Buzzer
Network	
Network Protocol	TCP/IP, HTTP, DDNS, SMTP, DHCP, PPPoE, UPnP, NTP, RTSP, RTMP, Onvif, P2P, HTTP push
Network Interface	2x RJ45 10/100Mbps network-adaptive Ethernet port
Auxiliary Interface	
SATA Interface	24x SATA interfaces(up to 8TB)
USB Interface	3x USB2.0 / 1x USB3.0
General	
User Management	Max support 32 users
Power Supply	ATX110-220V 400W 50-60Hz
Power Consumption	≤50W power consumption (without HDD)
Working Conditions	-10°C to 55°C / 10% to 90%