

NHC-7198K-8P

8-ch 4K H.265 Smart NVR

Highlights

- **8-ch** IP video input
- **80Mbps** Incoming bandwidth
- 1x **HDMI** output, 1x VGA output
- H.264/**H.265**/S265
- 1x SATA interfaces(up to **8TB**)



Specifications

8CH

H.265

8TB

Model	NHC-7198K-8P
Video and Audio	
Video Input	8-ch 4K/5MP/3MP/2MP/960P video input
Incoming Bandwidth	80Mbps
Video Output	1-ch HDMI(4K@30Hz), 1-ch VGA(1080P@60Hz)
Audio Input and Output	IPC Complex audio input, HDMI audio output
Decoding	
Video Compression	H.264/H.265/S265
Audio Compression	G.711
Synchronous Playback	1-ch 8MP / 4-ch 1080P / Max 9-ch Sub-stream
Alarm Management	
Alarm Port	Do not support
Schedule Type	Continuous, Schedule, Manual
Event	Motion Detection Alarm, Video Loss Alarm, Video Tampering Alarm (e-fence detection, human detection, line crossing, absent alarm, e-bike detection)
Action	Record, Email, Buzzer
Network	
Network Protocol	TCP/IP, HTTP, DDNS, SMTP, DHCP, PPPoE, UPnP, NTP, RTSP, RTMP, Onvif, P2P, HTTP push
Network Interface	1x RJ45 10/100Mbps network-adaptive Ethernet port
PoE Interface	8x RJ45 10/100Mbps network-adaptive IEEE 802.3af/at(15.4W/30W) Power over Ethernet port(DC 48V output voltage)
Auxiliary Interface	
SATA Interface	1x SATA interfaces(up to 8TB)
USB Interface	2x USB2.0 port (supports mouse, USB storage device, USB upgrade, import and export)
LED Indicator	Power, Record, Data transfer
General	
User Management	Max support 32 users
Power Supply	DC +52V/2.3A
Power Consumption	≤100W power consumption (without HDD)
Working Conditions	-10°C to 55°C / 10% to 90%