

GE1610-16P2SF

16 Gigabit Ethernet and PoE+, 2 Gigabit SFP Switch

Highlights

- 1-16 10/100/1000Mbps RJ45 support the 802.3af/at (PoE+)
- Support IEEE 802.3I, 802.3u, 802.3x, 802.3at, 802.3af, 802.3az
- Up to 30W PoE power for each port
- Support 8K MAC address
- Plug-and-play, no management required



Specifications

Model	GE1610-16P2SF
Hardware Specifications	
Ports	16x 10/100/1000M RJ45 ports 2x 1000M SFP ports
Power Supply	AC 100-240V 50/60Hz
Protocol Standards	IEEE 802.3i, 802.3u, 802.3x, 802.3at, 802.3af, 802.3az
Indicator Light	PoE indicators, Link/act indicators, Power
Network Medium	10Base-T: UTP category 3, 4, 5 cable (max. 100m) 100Base-Tx: UTP category 5, 5e cable (max. 100m) 1000Base-Tx: UTP category 5, 5e cable (max. 100m) 1000Base-Tx: MMF, SMF
Dimensions	440mm x 190mm x 44,5mm
Lightning Protection Level	4kv
PoE Port	16x 802.3af/at standard PoE ports
PoE Pin Definitions	1/2(+), 3/6(-)
PoE Power	225W
Total power	250W
Forwarding Mechanism	Store-and-Forward
Switching Capacity	36Gbps
Cache	4.1Mbit
Jumbo Frame	9KBytes
Forwarding Rate	26,784Mpps
MAC Address Table	8K
Environment	Operating Temperature: 0°C ~45°C Storage Temperature: -40°C ~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing