

# GE1610-4P2SF

4 Gigabit Ethernet and PoE+, 2 Gigabit SFP Switch

## Highlights

- 1-4 10/100/1000Mbps RJ45 support the 802.3af/at (PoE+)
- Support IEEE 802.3I, 802.3u, 802.3x, 802.3at, 802.3af, 802.3az
- Up to 30W PoE power for each port
- Support 8K MAC address
- Plug-and-play, no management required



## Specifications

<b>Model</b>	GE1610-4P2SF
<b>Hardware Specifications</b>	
<b>Ports</b>	4x 10/100/1000M RJ45 ports 2x 1000M SFP ports
<b>Power Supply</b>	AC 100-240V 50/60Hz
<b>Protocol Standards</b>	IEEE 802.3i, 802.3u, 802.3x, 802.3at, 802.3af, 802.3az
<b>Indicator Light</b>	PoE indicators, Link/act indicators, Power
<b>Network Medium</b>	10Base-T: UTP category 3, 4, 5 cable (max. 100m) 100Base-Tx: UTP category 5, 5e cable (max. 100m) 1000Base-T: UTP category 5e, 6 cable (max. 100m)
<b>Dimensions</b>	150mm x 83.5mm x 29mm
<b>Lightning Protection Level</b>	4kv
<b>PoE Port</b>	4x 802.3af/at standard PoE ports
<b>PoE Pin Definitions</b>	1/2(+), 3/6(-)
<b>PoE Power</b>	55W
<b>Total power</b>	65W
<b>Forwarding Mechanism</b>	Store-and-Forward
<b>Switching Capacity</b>	12Gbps
<b>Forwarding Rate</b>	8.928Mpps
<b>MAC Address Table</b>	2K
<b>Environment</b>	Operating Temperature: 0°C ~45°C Storage Temperature: -40°C ~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing