Navijin

DATASHEET

OPTICAL ACCESS (PON) / **EPON OLT**


NJO-2104X

4-port EPON OLT

PRODUCT PAGE

FTTH | FTTB | Cost-sensitive access

NJO-2104X



4	1:64	10G
EPON PORTS	SPLIT	UPLINKS

Overview

The Navijin NJO-2104X (4-port EPON OLT) is part of the Navijin Optical Access family. Entry EPON OLT for small FTTH and building networks. Cost-effective 1.25G EPON OLTs for FTTH and FTTB. It is managed centrally and supplied with warranty, local RMA and technical support through Navijin's Dubai hub and authorised partners.

Key Features

- IEEE 802.3ah EPON, symmetric 1.25 Gbps per PON port
- Split ratio up to 1:64 and 20 km reach; PX20, PX20+ and PX20++ optics
- Auto-discovery and interoperability with third-party ONUs
- DBA and SLA, per-ONU rate limiting, 802.1p QoS
- VLAN, QinQ, IGMP snooping and multicast VLAN
- EPON optical path protection and rogue ONU detection

Specifications

PON ports	4 × EPON
Uplinks	4 × GE RJ45, 4 × 10G SFP+ (1G compatible)
Max split	1:64
Backplane	128 Gbps
Power	Single or dual AC
Dimensions	442.5 × 280 × 44 mm (1U)
Weight	< 8 kg
Operating temp.	0 – 45 °C

Warranty & support Local RMA and technical support through our regional hub in Dubai and our authorized partners. Certificates and project pricing on request. **navijin.com · sales@navijin.com**

Rev. 2026-11. Specifications are subject to change without notice. Navijin and the Navijin logo are trademarks of Navijin Technology Co. All other trademarks are the property of their respective owners. © 2026 Navijin Technology Co. All rights reserved.