Navijin

DATASHEET

OPTICAL ACCESS (PON) / **GPON OLT**


NJO-3308X

8-port GPON OLT, 880G

PRODUCT PAGE

ISP FTTH | Hotels | Campuses | Residential towers

NJO-3308X



8	8 × 10G	AC/DC
GPON PORTS	UPLINKS	HOT-SWAP

Overview

The Navijin NJO-3308X (8-port GPON OLT, 880G) is part of the Navijin Optical Access family. Enterprise-aggregation GPON OLT with eight 10G uplinks and hot-swap AC/DC power. Rack-mount GPON OLTs with 4 to 16 PON ports and 10G uplinks. It is managed centrally and supplied with warranty, local RMA and technical support through Navijin's Dubai hub and authorised partners.

Key Features

- Full Layer 3 with BGP and IS-IS; ERPS ring protection
- ITU-T G.984 / G.988 GPON, 2.488 Gbps downstream / 1.244 Gbps upstream per port
- Split ratio up to 1:128 and 20 km reach; Class B+, C+ and C++ optics
- Auto-discovery of ONUs and interoperability with third-party ONTs
- DBA and SLA per ONU, upstream/downstream rate limiting, 802.1p QoS
- 4K VLANs, QinQ and flexible QinQ, IGMP snooping/proxy, MLD snooping

Specifications

PON ports	8 × GPON (SFP)
Uplinks	4 × GE RJ45, 8 × 1G/10G SFP+
Max split / reach	1:128 / 20 km
Backplane	880 Gbps
Layer 3	Static, RIP, OSPF, BGP, IS-IS, VRRP; IPv6
Power	AC 100–240 V or DC 36–72 V, dual hot-swap (100 W)
Dimensions	440 × 280 × 44 mm (1U)
Operating temp.	0 – 45 °C, 10–85% RH

Ordering Information

MODEL	DESCRIPTION
NJO-3308X	8 × GPON, 4 × GE, 8 × 10G SFP+, single AC PSU (2nd optional)
NJO-3308X-DC	As above with DC 36–72 V PSU
NPS-100A	Hot-swap AC power module, 100 W
NPS-100D	Hot-swap DC power module, 100 W

Warranty & support Local RMA and technical support through our regional hub in Dubai and our authorized partners. Certificates and project pricing on request. **navijin.com** · **sales@navijin.com**

Rev. 2026-11. Specifications are subject to change without notice. Navijin and the Navijin logo are trademarks of Navijin Technology Co. All other trademarks are the property of their respective owners. © 2026 Navijin Technology Co. All rights reserved.