Navijin

DATASHEET

OPTICAL ACCESS (PON) / **CHASSIS OLT**


NJO-7308

Multi-PON chassis OLT, 8 service slots

PRODUCT PAGE

Carrier networks | Large ISPs | Smart cities

NJO-7308



128	96 × 10G	Dual
PON PORTS	UPLINKS	CONTROL

Overview

The Navijin NJO-7308 (Multi-PON chassis OLT, 8 service slots) is part of the Navijin Optical Access family. High-capacity multi-service chassis for up to 128 GPON or EPON ports. Modular multi-service OLT chassis with redundant control and power. It is managed centrally and supplied with warranty, local RMA and technical support through Navijin's Dubai hub and authorised partners.

Key Features

- Fully modular: hot-swappable control, service, power and fan modules
- Dual control boards and redundant power (AC, DC or mixed) for carrier-grade uptime
- Single platform for FTTH, FTTB, FTTO and passive optical LAN
- Automatic fibre protection switching on trunk failure
- Layer 3 routing, IPv6, QinQ, multicast and per-ONU SLA
- Low power design reduces operating cost

Specifications

Slots	2 control, 8 service
Max PON ports	128 GPON or 128 EPON or 64 10G-EPON
Max uplinks	96 × 10G
Backplane	4 Tbps; MAC table 128K
Max split	1:128
Power	AC 90–264 V / DC 36–72 V, dual hot-swap
Dimensions	533.1 × 482.6 × 548 mm
Operating temp.	0 – 45 °C

Warranty & support Local RMA and technical support through our regional hub in Dubai and our authorized partners. Certificates and project pricing on request. **navijin.com** · **sales@navijin.com**

Rev. 2026-11. Specifications are subject to change without notice. Navijin and the Navijin logo are trademarks of Navijin Technology Co. All other trademarks are the property of their respective owners. © 2026 Navijin Technology Co. All rights reserved.