Navijin

DATASHEET

OPTICAL ACCESS (PON) / **CHASSIS OLT**

NJO-7502

XGS-PON chassis OLT, 2 service slots

PRODUCT PAGE

Carrier networks | Large ISPs | Smart cities

NJO-7502



32	1.8T	2+2
PON PORTS	BACKPLANE	REDUNDANCY

Overview

The Navijin NJO-7502 (XGS-PON chassis OLT, 2 service slots) is part of the Navijin Optical Access family. Compact modular chassis for up to 32 GPON or XG(S)-PON ports. Modular multi-service OLT chassis with redundant control and power. It is managed centrally and supplied with warranty, local RMA and technical support through Navijin's Dubai hub and authorised partners.

Key Features

- GPON, XG-PON, XGS-PON and combo service cards
- Fully modular: hot-swappable control, service, power and fan modules
- Dual control boards and redundant power (AC, DC or mixed) for carrier-grade uptime
- Single platform for FTTH, FTTB, FTTO and passive optical LAN
- Automatic fibre protection switching on trunk failure
- Layer 3 routing, IPv6, QinQ, multicast and per-ONU SLA

Specifications

Slots	2 control, 2 service, 2 power, 1 fan
Max PON ports	32 GPON / XG(S)-PON / combo
Max uplinks	8 × 10G, 4 × 100G
Max split	1:256
Backplane	1.8 Tbps
Power	Dual AC / DC / mixed, hot-swap
Operating temp.	0 – 45 °C

Warranty & support Local RMA and technical support through our regional hub in Dubai and our authorized partners. Certificates and project pricing on request. **navijin.com · sales@navijin.com**

Rev. 2026-11. Specifications are subject to change without notice. Navijin and the Navijin logo are trademarks of Navijin Technology Co. All other trademarks are the property of their respective owners. © 2026 Navijin Technology Co. All rights reserved.